



**Product
Specifications**

6.5 Meter Dual-Reflector Earth Station Antennas

Communications system integrators and designers can now bring their systems on line faster, more economically, and with superior performance with ASC Signal 6.5-meter Earth Station Antennas.

Excellent for high-density data, voice, communications networks, and broadcast applications, the ASC Signal 6.5m ESA features a formed dual reflector Gregorian system coupled with close-tolerance manufacturing techniques. This combination provides extremely accurate surface contour, exceptionally high gain, superior efficiency and closely controlled pattern characteristics.

Features:

- High Gain, Excellent Pattern Characteristics
- Advanced Gregorian Optics
- C, X and Ku band Operation
- Rugged Aluminum and Steel – 125 mph (200 kph) Wind Survival
- 3-year Warranty on All Structural

Components.

The 6.5 meter antenna is fully compliant with the FCC 25.209 specifications from 1° to 180° at C-band.

ASC Signal's ESAs provide maximum durability with minimal maintenance. The hot-dipped galvanized steel ground mount assembly ensures extended product life. Galvanized and stainless steel hardware maximize corrosion resistance.

For cost effective system expansion, available modular equipment options include anti-icing equipment as well as complete motorization and StepTrack control systems are available

Compliances:

- FCC regulation 25.209
- ITU-R, S.580-5 and S.465-5



Electrical

Operating Frequency Band	
<i>C-Band Receive</i>	3.400-4.2 GHz
<i>C-Band Transmit</i>	5.850-6.725 GHz

Gain, with 2 port linear combiner (dBi, ±0.2dB)

Rx Frequency	Rx Gain	Tx Frequency	Tx Gain
3.625 GHz	46.5	6.175 GHz	50.9
4.000 GHz	47.4	6.425 GHz	51.1
4.200 GHz	47.8	6.725 GHz	51.4

Polarization C-Band Linearly- or Circularly-Polarized
Polarization Discrimination, (Linearly-Polarized):

>35 dB across 1 dB beamwidth $19 - 25 \log \theta$ from 1.8° to 9.2°

Voltage Axial Ratio, C-Band, circularly-polarized with 4-port combiner
<1.06:1 across the 1 dB beamwidth <1.09 and 1.2 with 2-port

Beamwidth, Mid-band, Degrees	<i>C-Band</i>
<i>3 dB Receive (Transmit)</i>	.74 (.45)
<i>15 dB Receive (Transmit)</i>	1.46 (.87)

Antenna Noise Temperature - under clear sky conditions, at 68°F (20°C), with 2-port linear combiner.

<i>Elevation</i>	<i>Kelvin (C-Band)</i>
10°	39
30°	29
50°	26

Antenna VSWR, Transmit and Receive <1.3:1

Operating Frequency Band	
<i>Ku-band Receive</i>	Call
<i>Ku-band Transmit</i>	Call

Operating Frequency Band	
<i>X-band Receive</i>	Call
<i>X-band Transmit</i>	Call

Typical Shipping Information

Net Weight	6400 lb
Gross Shipping Weight (typical)	8101 lb
Shipping Volume (typical)	780 ft ³
Shipping Container	Standard 20 ft land/sea container

ASC Signal Corporation
1120 Jupiter Road, Suite 102
Plano, Texas 75074 USA

Telephone: +1-214-291-7654
Fax: +1-214-291-7655
Internet: www.ascsignal.com

G/T Performance (C-Band)

LNA/LNB Noise Temperature	65K	45K	30K
ES65 G/T at 10° EL (dB/K)	27.2	28.1	29.0

Based on a 2-port, linearly-polarized antenna configuration at 4 GHz and at 10° elevation under clear sky conditions.

Uplink ERP Capability (C-Band)

HPA Output (Watts)	125	500	3000
Uplink EIRP (dBW)	72.0	78.0	85.8

Based on a 2-port antenna configuration at 6.175 GHz and 0 dB allowance for waveguide (IFL) loss between the HPA and the antenna.

Mechanical

Feed Type	Dual-Reflector, Gregorian
Reflector Material	Precision-Formed Aluminum
Reflector Segments	16
Mount Type	El over AZ Tripod

Antenna Pointing Range, Coarse/(Continuous)

Elevation 0-90° (90°)

Azimuth 180° (120°)

Polarization 180° (180°)

Hub/Enclosure Dimensions

Diameter	52 in (1.22 m)
Depth	48.5 in (1.17 m)

Wind Loading, Survival

125 mph (200 km/h) in any position of operation

Wind Loading, Operational

45 mph (72 km/h), gusting to 65 mph (105 km/h) (motor drives)

Temperature, Operational -40° to 125°F (-40° to 52°C)

Rain 4 in (102 mm) per hour

Solar Radiation 360 BTU/hr/ft² (1135 Watts/m²)

Relative Humidity 100%

Shock and Vibration As encountered by commercial air, rail and truck shipment

Atmospheric Conditions Moderate coastal/industrial areas. Severe conditions require additional protection.

Typical Slab Foundation Information

Soil Bearing Capacity	2000 lb/ft ²
Reinforcing Steel	1780 lb
Concrete Compressive Strength	3000 lb/in ²
Foundation Size:	
<i>Length</i>	15.5 ft
<i>Width</i>	15.5 ft
<i>Depth</i>	2.0 ft
Concrete Volume	17.8 yd ³

shall not be disclosed or duplicated in whole or in part without express written consent of ASC Signal Corporation. All designs, specifications and availabilities are subject to change without notice. ESA65
© 2010 ASC Signal Corporation.

The technical data contained herein is proprietary to ASC Signal Corporation. This data